




- Heavy duty wire rope cutter designed for use in severe working conditions
- Open sided design allows for easy positioning of the cutter on the cable
- Blade shaped anvil cuts higher grade cable
- Corrosion resistant stainless steel body with Nitrotec coated alloy steel cylinder
- Long blade and anvil life ensures that tool maintenance is kept to a minimum
- Ideal for operation in confined spaces
- Can be used at any water depth


0

SOLE DISTRIBUTOR TO NTH & STH AMERICA

EBTOOL

0





- Cutting Capacity Steel wire ropes up to Ø38mm (1.5") with a maximum tensile strength of 1960N/mm². Individual wire strands must be a minimum of Ø1.5mm (1/16")
- Suitable for cutting wire rope, cables and umbilicals
- 220 bar maximum input pressure
- Supplied with 10k rated JIC No 4 fittings
- Approx weight in air 22kg
- Approx weight in water 19kg
- Swept volume cut stroke 0.5 litres
- Swept volume return stroke 0.4 litres

PHONE: 1.416.234.8671 **FAX:** 1.416.237.9279

EMAIL: info@webtool-subsea.com 61 Advance Rd., Unit 7, Toronto, Ontario, Canada M8Z 2S6

WEBTOOL-SUBSEA.COM



Webtool is a Trademark of Allspeeds Ltd Designed and Manufactured in the UK